

stavba: Lesní cesta "Nad bělidlem"

Tab. 4.

Souhrnná tabulka sjezdů														
staničení	pozn.:	1. zákl.	výška	2. zákl.	prodloužení sjezdu šíře/délka		plocha	frézování	ODK 100	Úph	250 HDK 63/125	200 HDK 32/63	100 HDK 32/63	50 ŠD 0/32
(km)		(m)	(m)	(m)	(m)	(m)	(m ²)	(m ²)	(m ²)	(m ²)	(m ²)	(m ²)	(m ²)	(m ²)
0,000	vpravo	4	40	4	0	0	160,00	0,0	160,0	160,0	160,0	0,0	160,0	160,0
0,000	vpravo ze skládky	6	10	3	0	0	45,00	0,0	45,0	45,0	45,0	0,0	45,0	45,0
0,084	rovně ze skládky	6	10	3	0	0	45,00	0,0	45,0	45,0	45,0	0,0	45,0	45,0
0,222	asfalt. - vpravo	6	10	3	0	0	45,00	45,0	45,0	45,0	0,0	45,0	0,0	45,0
0,866	asfalt. - vpravo zpět	6	10	3	3	10	75,00	75,0	0,0	75,0	0,0	75,0	0,0	75,0
0,905	vpravo ze skládky	6	10	3	0	0	45,00	0,0	45,0	45,0	45,0	0,0	45,0	45,0
1,294	vlevo	6	10	3	0	0	45,00	0,0	45,0	45,0	45,0	0,0	45,0	45,0
1,308	vpravo vpřed	6	30	3	0	0	135,00	0,0	135,0	135,0	135,0	0,0	135,0	135,0
1,345	vpravo	6	5	6	0	0	30,00	0,0	30,0	30,0	30,0	0,0	30,0	30,0
1,456	vlevo ze skládky	6	10	3	0	0	45,00	0,0	45,0	45,0	45,0	0,0	45,0	45,0
1,460	asfalt. - vpravo vpřed	6	10	3	0	0	45,00	45,0	0,0	45,0	0,0	45,0	0,0	45,0
1,800	asfalt. - vpravo zpět	6	10	3	0	0	45,00	45,0	0,0	45,0	0,0	45,0	0,0	45,0
1,800	asfalt. - vlevo vpřed	6	10	3	3	5	60,00	50,0	0,0	60,0	0,0	60,0	0,0	60,0
2,100	vpravo zpět ze skládky	6	10	3	3	17	96,00	0,0	96,0	96,0	96,0	0,0	96,0	96,0
2,119	vpravo ze skládky	6	10	3	0	0	45,00	0,0	45,0	45,0	45,0	0,0	45,0	45,0
2,119	vpravo ze skládky	6	10	3	0	0	45,00	0,0	45,0	45,0	45,0	0,0	45,0	45,0
Celkem:							plocha	frézování	ODK 100	Úph	250 HDK 63/125	200 HDK 32/63	100 HDK 32/63	50 ŠD 0/32
							1006,00	260,00	781,00	1006,00	736,00	270,00	736,00	1006,00