



48-Channel DMX light controller

- ✓ 96 Freely programmable and directly retrievable programs on four banks
- ✓ 4600 Scenes
- ✓ DMX 512 Standard
- ✓ Soft patch for all 512 channels
- ✓ 3 Working levels
- ✓ Mix chase
- ✓ Single chase function
- ✓ Blind home function speed
- ✓ Speed and fade control via sliders
- ✓ Sound-to-Light via built-in microphone or line-in
- ✓ Dimensions: 710 x 267 x 80 mm
- ✓ Height: 6 U
- ✓ Weight: 6.7 kg

4-Channel DMX Booster

- ✔ Universal optical DMX-512 splitter
- ✔ Distributes the incoming DMX signal into daisy chain configurations in four separate outputs with an additional "thru" port
- ✔ For easy connection the DB-1-4 has 3-pin and 5-pin XLR connectors
- ✔ The device can be installed into any 19" housing or via the M10 mount clamp on the back of the device
- ✔ The light controller has distinct LEDs to display the DMX signal status of each output and input

Specifications:

- ✔ 1x Input, 4x outputs: 3-pin and 5-pin
- ✔ An additional thru output: 3-pin and 5-pin (for connecting to other data streams)
- ✔ Electrical isolation between in- and output
- ✔ Format: 19" / 1U
- ✔ AC Power: Auto-switching 100 V - 240V 50/60Hz
- ✔ Dimensions (LxWxH): 483 x 134 x 46 mm
- ✔ Weight: 2.6 kg

Další informace

Type	Splitter
Distribution-type	1in4
Input	3/5-pole XLR
3-pole XLR Outputs	Yes
5-pole XLR Outputs	Yes
19"-capable	Yes
RDM-compatible	No
WDMX-capable	No

Mixer

- ✓ 18 Channels
- ✓ 60 mm Faders
- ✓ 6 Mic inputs with 48 V phantom power and 75 Hz low cut
- ✓ One compressor per mic channel
- ✓ Internal 24.Bit multi effect device with 16 presets
- ✓ Built-In USB sound card
- ✓ USB port for direct connection to the PC
- ✓ 9-Band Master EQ
- ✓ 4 Stereo inputs
- ✓ Three-band EQ with parametric mids
- ✓ 3 AUX (pre/post)
- ✓ Insert per channel
- ✓ Peak LED per channel
- ✓ Mute per channel
- ✓ 2 Track in / out
- ✓ XLR Main out
- ✓ 2 Subgroups with separate exit
- ✓ Mon Send Fader
- ✓ FX Return fader
- ✓ Internal power adapter
- ✓ Dimensions (H x W x D): 90 x 430 x 355 mm
- ✓ Weight: 4.64 kg
- ✓ Including 19" Rack kit

Další informace

Incl. Effects Unit	Yes
19" Rack Compatible	Yes
Mic Preamps	6
Stereo Inputs	4
Aux	3
Phantom power	Yes
Integrated Power Supply	Yes
Parametric	Yes
Digital Interface	Yes



Multicore system 16/4

- ✓ Stage-box in metal housing with permanently attached cable (shielded in pairs and as a whole)
- ✓ Separated snake-whip with split-protection
- ✓ Additional bending protection from printed shrinking tubes on each of the plug ends
- ✓ With Amphenol-plugs
- ✓ Length: 30 m
- ✓ Made in Germany

Další informace

Length In cm	30,00 m
Input	16
Returns	4
Snake	Yes
Stagebox	Yes
Cable Drum	No
Multipin Connector	No

Aktivní reproboxy - příloha č.5




Compact active fullrange cabinet

- ✓ Loudspeakers: 15"/ 1"
- ✓ Can also be used as a stage monitor
- ✓ Power: 1200 W Class D bi-amplified
- ✓ Maximum output level: 133 dB
- ✓ DSP with Plug and Play without complicated layered menus
- ✓ Integrated control over functions such as EQ, X-Over, limiters, EQ presets (Flat/Boost)
- ✓ Tone control for quick adjustment of voicing (Music/speech)
- ✓ FIR - Crossover
- ✓ 90° x 55° CD horn
- ✓ Steady wooden cabinet
- ✓ M8 rigging points for easy installation
- ✓ Dimensions: 47 x 62 x 45 cm
- ✓ Weight: 22.6 kg
- ✓ Made in Germany

Další informace

Multifunctional Housing	Yes
Pole Mount	Yes
Flyable	Yes
Woofer size	1x 15"
Tweeter, 1" and Larger	Yes
Weight in kg	22,6 kg

Stojan - příloha č.6



Speaker Tripod

- ✔ Suitable for Roland battery amps BA-330 and KC-110
- ✔ Adjustable height from 925 - 1425 mm
- ✔ Max. load: 40 kg
- ✔ Tube diameter: 38 mm
- ✔ Material: Aluminium
- ✔ Weight: 2.3 kg
- ✔ Compatible with BA-330, KC-150/60, AC-90/60, SA-300 amp head
- ✔ Includes carry bag

Note: Not suitable for 35 mm speakers.

Další informace

Pole diameter	38 mm
2 pieces Set	No
Material	Aluminium
Wind-Up Stand	No
Ringlock	No
Pneumatic	No
Foot Construction	Tripod
Color	Black

Světla na obarvení scény - příloha č.7



Compact Spotlight

- ✓ Provides a complete 3-in-1 RGB colour mix with rich colours and a perfect blend
- ✓ Saves lots of space both during transport and when in use
- ✓ Fully digitally controlled - can be controlled via DMX as well as by music
- ✓ At smaller events, can be operated in Master/Slave mode

Specifications:

- ✓ Power: Lumens: 1540, Lux @ 2m: 2230
- ✓ Max distance: 20 m
- ✓ Light Source: LED system: 7 x 3-in-1 LED
- ✓ Input current: 350 mA
- ✓ Update rate: 3.9 kHz
- ✓ Mains voltage: 100 - 240 V AC
- ✓ Power consumption: 50 W
- ✓ Control mode: DMX 512
- ✓ DMX channels: 3, 4, 8
- ✓ Optical system: Dimmer: 0-100%
- ✓ Strobe: 0 - 20 Hz
- ✓ Beam angle: 40°

Physical aspects:

- ✓ Dimensions: 290 x 275 x 115 mm
- ✓ Weight: 2.6 kg
- ✓ Housing: Aluminum and iron
- ✓ Network connections: IEC
- ✓ Data connections: XLR 3-pin
- ✓ Cooling: Cooling element made of aluminium
- ✓ Safety: Operating temperature -20 - 40 °C
- ✓ Colour: Dark grey and black

Další informace

Construction Type	Flat PAR
Number of LEDs	7
power of the single LED	3 W
Color mixing	RGB
LED Type	x-in-1
Floor housing	Yes
Fanless	Yes
remote control	not supported
wireless DMX	No
Housing Color	Silver

Převodník FTP/HDMI - příloha č.8

Vlastnosti:

- Přenáší HDMI signál až do vzdálenosti 70 m pomocí jednoho CAT kabelu
- Podporuje přenos 4K UHD videa až do vzdálenosti 40 m (3840x2160/30Hz 4:4:4, 4096x2160/24Hz 4:4:4, a 4K/60Hz 4:2:0)
- Podporuje všechna standardní rozlišení videa včetně VGA-WUXGA a 480i-4K
- Podporuje 3D signály
- Podporuje všechny známé HDMI audio formáty včetně Dolby TrueHD, Dolby Atmos, Dolby Digital Plus a DTS-HD Master Audio
- Obousměrné IR na všech vstupech a výstupech
- Podporuje obousměrné PoH (PoE) pro napájení extenderu ať už z vysílače nebo přijímače
- HDCP 2.2 kompatibilní

Vstupy:

Přijímač: 1x HDBaseT RJ45 1x 3,5 mm stereo jack (IR port)

Vysílač: 1x HDMI typ A, 19-pin, Female 1x 3,5 mm stereo jack (IR port)

Výstupy

Přijímač: 1x HDMI typ A, 19-pin, Female 1x 3,5 mm mono jack

Vysílač: 1x HDBaseT RJ45 1x 3,5 mm mono jack

Zdroj napájení: 12V / 2A DC

Spotřeba: 9,5W

Rozměry (mm): 105 (š) x 75 (h) x 26 (v)

Provozní teplota: 0oC až 40oC

Skladovací teplota: -20oC až 60oC

Hmotnost: 250g

Projektor - příloha č.9

Úhlopříčka a rozlišení

Rozlišení	1280 × 800 px
-----------	---------------

Poměr stran	16:10
-------------	-------

Kontrast	30 000:1
----------	----------

Úhlopříčka obrazu (min.)	90,53 cm (35,64 ")
--------------------------	--------------------

Úhlopříčka obrazu (max.)	769,57 cm (302,98 ")
--------------------------	----------------------

Rozlišení

<u>Nativní rozlišení</u>	1280 × 800 px
--------------------------	---------------

Poměr stran	16:10
-------------	-------

Projekční plocha

<u>Projekční vzdálenost (min.)</u>	0,4 m
------------------------------------	-------

<u>Projekční vzdálenost (max.)</u>	3,4 m
------------------------------------	-------

Projekční vzdálenost	Méně než 1 m, 1 m - 1,99 m, 2 m - 2,99 m, 3 m - 3,99 m
----------------------	--

<u>Úhlopříčka obrazu (min.)</u>	91 cm (35,83 ")
---------------------------------	-----------------

Úhlopříčka obrazu (max.)	770 cm (303,15 ")
--------------------------	-------------------