



Altro is the first safety flooring  
manufacturer to recycle  
traditional safety flooring in-house




altro

the future is safer with altro


# Altro Stronghold™ 30/Altro K30

Safety Flooring / Suelos de Seguridad / Sicherheitsbodenbelag

Altro Stronghold™ 30/  
Altro K30  
contains recycled material




Monsoon K30153  
WR81 / A1M81 / LRV24




Dolphin K3010  
WR86 / A1M86 / LRV21



Abyss K3001  
WR100 / A1M100 / LRV7




Oyster K30215  
WR20 / A1M20 / LRV36




Skyline K30332  
WR52 / A1M52 / LRV24




Tundra K30500  
WR153 / A1M239 / LRV17




Camel K3017  
WR64 / A1M239 / LRV26




Surf K30412  
WR71 / A1M71 / LRV20




Lagoon K30910  
WR39 / A1M34 / LRV7



Maple K30522  
WR24 / A1M27 / LRV31



Russet K30262  
WR41 / A1M41 / LRV14



Velvet K30365  
WR256 / A1M148 / LRV8

Exact Material Match with samples cannot be guaranteed.


















No podemos garantizar que el material del suelo de seguridad coincida exactamente con el de las muestras.  
Eine exakte Übereinstimmung des Materials mit Mustern kann nicht garantiert werden.

[www.altro.com](http://www.altro.com)

A+ BRE Generic Green Guide  
Rating for Safety Flooring,  
full details available at  
[www.thegreenguide.org.uk](http://www.thegreenguide.org.uk)

All Altro safety flooring  
contains recycled content




Flooring Type Tipo de pavimento Belagsart		EN 13845/ EN 13553	Safety flooring Suelo de seguridad antideslizante Sicherheitsbodenbelag
Classification for use Areas de uso Einsatzbereiche		EN 685	34 & 43 34 y 43 34 & 43
Slip Resistance Resistencia al deslizamiento Rutschsicherheit*		TRRL / CTE EN 13845 EN 13893 DIN 51130	> 50. Class 3 / Clase 3 / Klasse 3 (CTE) ES DS R12
Thickness Espesor Total Gesamtdicke		EN 428	3 mm
Wear Layer Capa de uso Nutzschicht		EN 429	3 mm
Weight Peso Flächengewicht		EN 430	3.4 kg/m <sup>2</sup> 3,4 kg/m <sup>2</sup> 3,4 kg/m <sup>2</sup>
Roll Dimensions Dimensiones del rollos Rollenabmessungen		EN 426	2 m x 15 m = 30 m <sup>2</sup>
Light Fastness Resistencia a la luz Lichtechtheit		EN 20105-B02	> 6
Sound Insulation Aislamiento acústico Trittschal		ISO 140-8	10 dB
Wear Resistance Abrasión Verschleißverhalten		EN 13845 EN660-2	Group 34/43, Grupo 34/43 / Gruppe 34/43 Group T/ Grupo T/ Gruppe T
Indentation Punzonamiento Reiteindruck		EN 433	< 0.10mm
Fire Performance Reacción al fuego Brandverhalten		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl s1 > 8kw/m <sup>2</sup> Pass Clase Bfl s1 > 8kw/m <sup>2</sup> Conforme Klasse Bfl-s1 > 8kw/m <sup>2</sup> , bestanden
Chemical Resistance Resistencia a los productos químicos Chemikalieneinwirkung**		EN 423	Good Buena beständig
Castor Chair Abrasion Huellas de sillas de ruedas Stuhlrollenbeanspruchung		EN 425	Pass Conforme geeignet
Under floor heating Calefacción por el suelo Fußbodenheizung		EN 12667	Suitable Apto geeignet
Electrical Behaviours Características eléctricas Elektrisches Verhalten		EN1815	< 2 kV Antistatic < 2 kV Antiestáticas < 2 kV antistatisch
VOC Emissions Emisiones de VOC VOC Emissionen		prEN 15052 Section 01350 AgBB/DIBt	Low/Pass/Approved Baja/Conforme/Aprobado gering/geeignet/zugelassen

\*For wet areas where bare foot slip resistance is required such as showers and swimming pool surrounds, we recommend the use of Altro Marine™ 20/T20. \*\*Caution Ketone/Aromatic Solvents. Please contact Altro for further technical advice regarding staining and chemical resistance. Contains Biocide.

## Installation and Maintenance

All Installations in accordance with Altro safety flooring instructions and Local Codes of Practice. Please refer to Altro Cleaning Card for maintenance advice. Failure to install and maintain Altro floors in accordance with installation instructions can affect its performance and slip resistance. Floors should be protected from other trades and thoroughly cleaned before handover.



For further technical information please visit [www.altro.com](http://www.altro.com)

Si desea obtener más información técnica, visite [www.altroscandess.com](http://www.altroscandess.com)

Weitere technische Informationen finden Sie auf unserer Website [www.altro.de](http://www.altro.de)

Altro, the future is safer with altro, Altro Stronghold 30/Altro K30, Altro Marine 20/T20 and Altrosan are trademarks of Altro Limited.

EN13845