

VÝKAZ KONSTRUKČNÍ OCELI

POČET	PROFIL	DĚLKA			NORMA	HMOTNOST		
		ks [m]	celkem [m]	TRÍDA OCELI		ks [kg]	celkem [kg]	
12	D30	0.17	1.98	S355		0.87	10.49	
1	IPE140	0.10	0.10	S355		1.31	18.18	
1	IPE140	0.10	0.10	S355		1.31	18.18	
1	IPE140	0.10	0.10	S355		1.31	18.18	
12	IPE140	0.10	1.22	S355		1.31	15.76	
1	IPE140	0.11	0.11	S355		1.38	1.38	
1	IPE140	0.11	0.11	S355		1.38	1.38	
1	IPE140	0.14	0.14	S355		1.83	1.83	
1	IPE140	0.14	0.14	S355		1.83	1.83	
12	IPE140	0.14	1.70	S355		1.83	21.94	
1	IPE140	0.30	0.30	S355		3.93	3.93	
1	IPE140	0.78	0.78	S355		10.99	10.99	
1	IPE140	0.82	0.82	S355		10.94	10.94	
1	IPE140	0.83	0.83	S355		10.74	10.74	
1	IPE140	1.07	1.07	S355		13.71	13.71	
1	IPE140	1.10	1.10	S355		14.16	14.16	
1	IPE140	1.15	1.15	S355		14.74	14.74	
9	IPE140	1.30	11.74	S355		16.79	151.09	
2	IPE140	1.34	2.68	S355		17.28	34.55	
11	IPE140	1.43	15.73	S355		18.41	202.51	
2	IPE140	1.51	3.01	S355		19.38	38.75	
1	IPE140	1.63	3.06	S355		19.72	39.45	
2	IPE140	1.54	3.08	S355		19.85	39.70	
1	IPE140	1.55	1.55	S355		19.95	19.95	
1	IPE140	1.56	1.56	S355		20.15	20.15	
1	IPE140	1.58	1.58	S355		20.41	20.41	
1	IPE140	1.59	1.59	S355		20.43	20.43	
1	IPE140	1.62	1.62	S355		20.84	20.84	
3	IPE180	0.11	0.32	S355		2.03	6.08	
1	IPE180	0.12	0.12	S355		2.25	2.25	
3	IPE180	0.14	0.41	S355		2.59	7.77	
1	IPE180	1.50	1.50	S355		28.14	28.14	
1	IPE180	1.61	1.61	S355		30.30	30.30	
1	IPE180	1.62	1.62	S355		30.39	30.39	
1	IPE180	1.65	1.65	S355		31.05	31.05	
3	IPE180	3.01	9.03	S355		96.49	289.47	
6	IPE200	3.28	19.68	S355		73.38	440.29	
1	JC292	0.25	0.25	S355		0.35	0.35	
1	JC292	0.32	0.32	S355		0.46	0.46	
2	JC292	0.53	1.07	S355		0.77	1.55	
3	JC292	0.55	1.65	S355		0.79	3.92	
25	JC292	0.63	15.69	S355		0.89	22.20	
25	JC50/5	1.13	28.22	S355		7.89	197.19	
6	JC50/5	1.14	6.82	S355		7.93	47.56	
2	JC50/5	1.24	2.47	S355		8.74	17.49	
1	JC50/5	1.27	1.27	S355		8.78	8.78	
5	JC50/5	1.28	6.40	S355		8.78	43.79	
132	JC50/5	1.43	188.76	S355		10.10	1333.60	
1	JC50/5	1.55	1.55	S355		10.70	10.70	
106	JC50/5	3.34	16.68	S355		23.19	115.92	
1	JC50/5	3.64	3.64	S355		25.80	25.80	
5	JC80/5	1.43	7.15	S355		16.84	84.19	
10	JC80/50/5	0.15	1.50	S355		1.18	11.77	
16	JC80/50/5	0.20	3.20	S355		1.41	22.91	
106	JC80/50/5	0.21	21.20	S355		1.53	162.26	
120	JC80/50/5	0.30	36.00	S355		2.59	310.86	
12	JC80/50/5	0.40	4.80	S355		3.06	36.74	
6	JC120/50/5	0.80	4.80	S355		10.05	60.29	
3	JC140/5	0.05	0.15	S355		1.25	3.76	
1	JC140/5	5.55	5.55	S355		140.24	140.24	
4	JC140/5	5.55	22.22	S355		140.24	560.96	
1	JC140/5	7.74	7.74	S355		195.06	195.06	
4	JC140/5	7.74	30.97	S355		194.85	778.62	
5	JC140/50/4	0.14	0.71	S355		1.71	8.55	
9	JC140/50/4	0.14	1.28	S355		1.71	15.41	
105	JC140/50/4	0.14	14.91	S355		1.71	179.78	
1	JC140/50/4	0.74	0.74	S355		8.97	8.97	
4	JC140/50/4	0.74	2.96	S355		8.98	35.90	
7	JC140/50/4	0.78	5.45	S355		9.39	65.75	
6	JC140/50/4	0.83	4.98	S355		10.00	60.00	
6	JC140/50/4	1.07	6.39	S355		12.84	77.05	
3	JC140/50/4	1.10	3.30	S355		13.28	39.78	
3	JC140/50/4	1.10	3.30	S355		13.27	39.80	
6	JC140/50/4	1.15	6.87	S355		13.81	82.84	
16	JC140/50/4	1.26	20.22	S355		15.24	243.85	
15	JC140/50/4	1.29	19.41	S355		15.60	234.04	
8	JC140/50/4	1.30	10.39	S355		15.86	125.30	
8	JC140/50/4	1.30	10.39	S355		15.86	125.30	
16	JC140/50/4	1.51	24.08	S355		18.15	290.35	
8	JC140/50/4	1.55	12.40	S355		18.69	148.61	
8	JC140/50/4	1.58	12.68	S355		19.11	152.89	
8	JC140/50/4	1.61	12.92	S355		19.47	155.78	
8	JC140/50/4	2.27	22.37	S355		27.37	217.37	
2	JC140/70/7	3.10	6.21	S355		66.88	133.77	
4	JC140/70/7	3.15	12.60	S355		67.85	271.41	
7	JC140/70/7	5.55	38.88	S355		119.66	837.60	
3	JC140/70/7	6.09	18.28	S355		130.72	392.17	
3	JC140/70/7	6.09	18.28	S355		130.75	392.24	
7	JC140/70/7	7.74	54.20	S355		166.29	1164.01	
2	JC180/50/5	0.03	0.07	S355		0.17	0.34	
6	JC180/50/5	1.09	6.57	S355		21.06	126.38	
6	JC180/50/5	1.41	8.46	S355		22.24	163.47	
6	JC180/50/5	1.65	9.91	S355		32.00	192.02	
4	JC180/50/5	1.97	7.87	S355		38.19	152.74	
6	JC180/50/5	3.73	22.39	S355		72.41	434.44	
4	JC180/50/5	3.73	14.65	S355		72.41	289.63	
2	JC180/50/5	3.80	7.60	S355		71.81	143.62	
1	L60/5	0.79	0.79	S355		3.62	3.62	
2	L60/5	0.87	1.74	S355		3.99	7.97	
3	L60/5	0.99	2.96	S355		4.51	13.54	
3	L60/5	1.01	3.02	S355		4.60	13.81	
3	L60/5	1.14	3.42	S355		5.21	15.62	
1	L60/5	1.29	1.29	S355		5.90	5.90	
3	L60/5	1.30	3.91	S355		5.95	17.86	
2	L60/5	1.31	2.61	S355		5.97	11.94	
1	L60/5	1.33	1.33	S355		6.00	6.00	
3	L60/5	1.36	4.07	S355		6.19	18.58	
3	L60/5	1.36	4.07	S355		6.19	18.58	
3	L60/5	1.37	4.12	S355		6.20	18.84	
2	L60/5	1.39	2.79	S355		6.37	12.74	
3	L60/5	1.40	4.19	S355		6.38	19.13	
1	L60/5	1.57	1.57	S355		7.16	7.16	
1	L60/5	1.59	1.59	S355		7.27	7.27	
1	L60/5	1.61	1.61	S355		7.34	7.34	
1	L60/5	1.61	1.61	S355		7.37	7.37	
3	L60/5	1.91	5.73	S355		8.73	26.18	
1	L60/5	2.22	2.22	S355		10.15	10.15	
2	L60/5	2.22	4.45	S355		10.15	20.30	
1	L60/5	2.24	2.24	S355		10.21	10.21	
1	L60/5	2.28	2.28	S355		10.41	10.41	
1	L60/5	2.29	2.29	S355		10.48	10.48	
1	L60/5	2.29	2.29	S355		10.48	10.48	
1	L60/5	2.35	2.35	S355		10.72	10.72	
1	L60/5	2.36	2.36	S355		10.80	10.80	
3	TR44/5	0.03	0.09	S355	EN 10219	0.15	0.44	
2	TR44/5	0.04	0.08	S355	EN 10219	0.18	0.36	
2	TR44/5	0.07	0.14	S355	EN 10219	0.32	0.63	
5	TR44/5	0.08	0.39	S355	EN 10219	0.36	1.81	
1	TR44/5	0.14	0.14	S355	EN 10219	0.65	0.65	
2	TR44/5	0.24	0.49	S355	EN 10219	1.14	2.29	
3	TR44/5	0.32	0.95	S355	EN 10219	1.47	4.41	
1	TR44/5	0.32	0.32	S355	EN 10219	1.51	1.51	
3	TR44/5	0.39	1.16	S355	EN 10219	1.81	5.44	
3	TR44/5	1.16	3.48	S355	EN 10219	5.43	16.30	
3	TR44/5	1.45	4.35	S355	EN 10219	6.79	20.37	
3	TR44/5	1.61	1.61	S355	EN 10219	7.40	7.40	
3	TR44/5	1.72	5.16	S355	EN 10219	8.07	24.20	
1	TR44/5	2.02	2.02	S355	EN 10219	9.48	9.48	
1	TR44/5	2.47	2.47	S355	EN 10219	11.56	11.56	
3	TR44/5	3.06	9.17	S355	EN 10219	14.32	42.96	
1	TR44/5	3.36	3.36	S355	EN 10219	15.75	15.75	
2	TR44/5	3.37	6.74	S355	EN 10219	15.79	31.58	
3	TR44/5	3.40	10.19	S355	EN 10219	15.92	47.75	
1	TR44/5	3.42	3.42	S355	EN 10219	16.03	16.03	
3	TR44/5	3.44	10.30	S355	EN 10219	17.07	51.21	
3	TR44/5	3.65	10.96	S355	EN 10219	17.12	51.37	
2	TR44/5	4.90	9.80	S355	EN 10219	22.97	45.95	
1	TR44/5	6.36	6.36	S355	EN 10219	29.72	29.72	
2	TR44/5	8.11	16.22	S355	EN 10219	37.92	75.85	
1	UPE140	0.10	0.10	S355	DIN 1026-2	1.40	1.40	
1	UPE140	0.21	0.21	S355	DIN 1026-2	3.06	3.06	
2	UPE140	0.25	0.49	S355	DIN 1026-2	3.57	7.14	
1	UPE140	0.28	0.28	S355	DIN 1026-2	4.07	4.07	
1	UPE140	0.28	0.85	S355	DIN 1026-2	4.10	12.31	
2	UPE140	0.31	0.62	S355	DIN 1026-2	4.48	8.95	
1	UPE140	0.35	0.35	S355	DIN 1026-2	5.11	5.11	
1	UPE140	0.78	0.78	S355	DIN 1026-2	11.32		